# **MATERIAL SAFETY DATA SHEET**



# SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: QuikPlastik®
CAS Number: Mixture

Hazard Rating: Health: 1 Fire: 1 Reactivity: 0 PPI: B

Company Identification: POLYMERIC SYSTEMS, INC.

723 WHEATLAND STREET PHOENIXVILLE PA 19460

Contact: I. David Crossan

**Telephone/Fax:** (610) 935-1170 / (610) 935-7123

Emergency Phone (24 Hour): (800) 424-9300 (610) 935-1170

Chemtrec (24 Hour): (800) 424-9300

Preparer: I. David Crossan

Technical Director

Product Class: EPOXY PUTTY Trade Name: QuikPlastik®

Product Code: 4755

Shipping Name: PUTTY, NMFC 150110

# SECTION II - INGREDIENT AND HAZARD INFORMATION

Ingredient Name CAS Number Percent TSCA

Diglycidyl ethers of bisphenol A resins 67989-52-0 15 – 40 Y

HMIS Health: 2 Fire: 1 Reactivity: 0 PPI: B

Tri(dimethylaminomethyl)phenol 90-72-2 0.5-1.5 Y

HMIS Health: 3 Fire: 1 Reactivity: 1 PPI: D

\*\*\* ALL Ingredients in this product are listed in the T.S.C.A. Inventory

## SECTION III - PHYSICAL DATA

Form: Putty
Appearance/Color: Blue/White
Odor: Sulfur, Mercaptan
Solubility (in water): Insoluble in Water

Solubility (in water):

pH Value:

Boiling Range:

Vapor Pressure (mmHg):

Melting Point:

Evaporation Rate:

Non Volatile

Non Volatile

% Volatile: < 1%</li>
VOC: < 1%</li>
Heavy Elements (ppm): 0.
Specific Gravity: 1.9

#### NOTE:

The physical data represented above are typical values and should not be construed as a specification. For additional physical data and details on use, please obtain a technical data sheet for this product.

MSDS Name QuikPlastik® Version Number 3 Page 1 of 4 MSDS Number: 4-755 MSDS Date: 11-13-2002

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Class:

Flash Range: Not Applicable Explosive Range: Not Applicable

### **EXTINGUISHING MEDIA:**

Water spray, foam, CO2, dry chemicals.

### **UNUSUAL HAZARDS:**

Aldehydes, acids, and oxides of carbon, nitrogen, and sulfur.

#### FIRE FIGHTING

Fire Fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved positive pressure self-contained breathing apparatus (SCBA) and full protective clothing.

## SECTION V - HEALTH HAZARD DATA

| Diglycidyl ethers of bisphenol A resins | Route        | Species                     | Exposure and Dose                   |
|---|--------------|-----------------------------|-------------------------------------|
| Tri(dimethylaminomethyl)phenol          | Oral<br>Skin | Rat, adult<br>Rabbit, adult | LD50 5000 mg/Kg<br>LC50 20000 mg/Kg |
| m(uimeuryianiinomeuryi)phenoi           | Oral         | Rat, adult                  | LD50 1630 mg/Kg                     |

### PERMISSIBLE EXPOSURE LEVEL:

Not Evaluated

# **EFFECTS OF OVEREXPOSURE:**

Inhalation: None

Ingestion:Irritation of intestinal tractSkin Contact:Possible irritant and sensitizer.Eye Contact:Possible irritant and sensitizer.

FIRST AID:

Inhalation:Remove to fresh air.Ingestion:Seek medical advice.

**Skin Contact:** Wash with plenty of soap and water.

**Eye Contact:** Flush with water for at least 15 minutes. Seek medical advice.

NOTE:

Never give anything by mouth to an unconscious person.

## SECTION VI - STABILITY AND REACTIVITY DATA

**Stability:** This product is stable

Hazardous Polymerization: Hazardous polymerization will not occur

**INCOMPATIBILITY** 

None

#### **CONDITIONS TO AVOID:**

None

### **HAZARDOUS DECOMPOSITION PRODUCTS:**

Aldehydes, acids, and oxides of carbon, nitrogen, and sulfur.

MSDS Name QuikPlastik® Version Number 3 Page 2 of 4 MSDS Number: 4-755 MSDS Date: 11-13-2002

# SECTION VII - SPILL AND LEAK PROCEDURES

#### STEPS TO BE TAKEN:

Spills or leaks: Dispose of in normal manner.

### **WASTE DISPOSAL METHOD:**

Incinerate in furnace or bury in landfill in accordance with all applicable regulations; not a hazardous waste.

# SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits** 

ACGIH TLV ACGIH TLV-C ACGIH STEL OSHA STEL OSHA PEL

Diglycidyl ethers of bisphenol A resins

N/est N/est N/est N/est

Tri(dimethylaminomethyl)phenol

5.00 PPM N/est N/est N/est N/est

**PROTECTIVE EQUIPMENT TYPES:** 

**Eyes:** Safety glasses or goggles.

**Respiratory:** None required unless sanding or abrading.

**Gloves:** Appropriate impervious gloves. Because a variety of protective gloves exist,

consult glove manufacturer to determine the proper type for a specific

operation.

Other: None Required.

**VENTILATION:** 

General Mechanical: None Required

**Local Exhaust:** Only if heated above 100°F (38°C)

## SECTION IX - HANDLING AND STORAGE

Storage Temperature: < 90F (32C)

**Storage Conditions**: Store in cool, dry, well-ventilated area.

Transfer: No special precautions are needed. Follow good manufacturing and handling practices.

**Personal Hygiene:** Wash thoroghly after handling, especially before eating, drinking, smoking and using restroom facilities. Wash contaminated goggles, faceshield, and gloves. Professionally launder contaminated clothing before re-use.

**Empty container precautions:** Attention! This container can be hazardous when empty. Follow label cautions even after the container is empty since empty containers could retain product residues. Do not re-use empty containers for food, clothing, or products for human or animal consumption, or where skin contact can occur.

## SECTION X - REGULATORY INFORMATION

#### **SARA TITLE III SECTION 313:**

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name CAS Number Percent

None Known

### Right-to-Know:

The non-hazardous ingredients in this product subject to Pennsylvania, New Jersey, and/or Massachusetts Right-to-Know laws are:

MSDS Name QuikPlastik® Version Number 3 Page 3 of 4

**MSDS Number:** 4-755 **MSDS Date:** 11-13-2002

CAS 14807-96-6 65997-17-3 Trade Secret

67762-90-7

Chemical
Magnesium Silicate Hydrate
Sodium calcium magnesium silicate
Polyether Polymercaptan
Amorphous Silica

NOTE:

**USERS RESPONSIBILITY:** A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions - in addition to those described herein - are required. Any health hazard and safety information herein should be passed on to your customers or employees as the case may be.

DISCLAMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representaion or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information refers. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

MSDS Name QuikPlastik® MSDS Number: 4-755

Version Number 3 MSDS Date: 311-13-2002